

Printing date 23.02.2017 Version number 1 Revision: 23.02.2017

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: TopDent Dry-Sep
- · Article number: according to Catalog
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU20 Health services
- · Environmental release category ERC2 Formulation into mixture
- · Application of the substance / the mixture Dental material
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kentzler-Kaschner Dental GmbH

Mühlgraben 36 D-73479 Ellwangen Tel: +49/7961/90730 Fax: +49/7961/52031 E-Mail: info@kkd-topdent.de

· Further information obtainable from:

During normal business hours

Monday-Thursday 08:30 - 12:30 and 13:00 - 16:30 CET

Friday 08:30 - 12:30 and 13:00 - 15:00 CET

• 1.4 Emergency telephone number: Vergiftungs-Informations-Zentrale Freiburg, Tel. +49 761 19240

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling: propan-2-ol
- $\cdot \textit{Hazard statements}$

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

(Contd. on page 2)



Printing date 23.02.2017 Version number 1 Revision: 23.02.2017

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description**: Dental material

· Dangerous compone	ents:	
CAS: 67-63-0	propan-2-ol	10-30%
EINECS: 200-661-7	(A) Flam, Lia, 2, H225; (1) Eve Irrit, 2, H319; STOT SE 3, H336	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information:

Take affected persons out of danger area and lay down.

Do not leave affected persons unattended.

Take affected persons out into the fresh air.

- · After inhalation: Take affected persons into fresh air and keep quiet.
- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Inform doctor. Do not give milk or fatty oils.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture Carbon dioxide (CO2)
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 3)



Printing date 23.02.2017 Version number 1 Revision: 23.02.2017

(Contd. of page 2)

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: None.
- $\cdot$  7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

#### 67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:

DGUV 112-190 Breathing apparatus

Suitable respiratory protective device recommended.

Filter type A2

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Fluorocarbon rubber (Viton)

(Contd. on page 4)



Printing date 23.02.2017 Version number 1 Revision: 23.02.2017

(Contd. of page 3)

Butyl rubber, BR

Recommended material thickness: Butylkautschuk: 0,50 mm +/- 0,10 mm Fluorkautschuk: 0,75 mm +/- 0,10 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Basis: DGUV 212-007

Permeation (Fluorkautschuk): + Level 6 (> 240 min) Permeation (Butykautschuk): + Level 6 (> 480 min)

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Butyl rubber, BR

- · Not suitable are gloves made of the following materials: PVC gloves
- · Eye protection: Goggles recommended during refilling

CECTION		TO I	. 1	1	- 1			
<b>SECTION</b>	y٠	Phys	ıcaı	ana	C I	1emicai	nro	nerties
DECITOR	~ •	10,0		CUITUCU	~	verious cut	P 1 V	Perteb

9.1 Information on basic physical a	nd chemical properties
· General Information	
· Appearance: Form:	Fluid
Colour:	Colourless
· Odour:	Like alcohol
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling ra	ange: 82 °C
· Flash point:	20 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	425 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
· Explosion limits:	
Lower:	2.0 Vol %
Upper:	13.4 Vol %
· Vapour pressure at 20 °C:	43 hPa
· Density at 20 °C:	0.87 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.

(Contd. on page 5)



Printing date 23.02.2017 Version number 1 Revision: 23.02.2017

		(Contd. of page 4)
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Fully miscible.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	30.0 %	
· 9.2 Other information	No further relevant information available.	

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Open fire, hot surfaces, high temperatures
- · 10.5 Incompatible materials: oxidants, acids, bases
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Subacute to chronic toxicity:

97489-15-1 Sulfonsäure, C14-17, sec-alkan, Natriumsalz

Oral, NOAEL (28 d): 4000 mg/kg/d (Ratte)

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot \textit{Reproductive toxicity Based on available data, the classification criteria are not met.}\\$
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 6)



Printing date 23.02.2017 Version number 1 Revision: 23.02.2017

(Contd. of page 5)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

18 01 06\* | chemicals consisting of or containing hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN-Number ADR, IMDG, IATA	UN1219
14.2 UN proper shipping name ADR IMDG, IATA	1219 ISOPROPANOL (ISOPROPYL ALCOHOL) ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group	·
ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	3
EMS Number:	F-E,S-D
Stowage Category	B
14.7 Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.

(Contd. on page 7)



Printing date 23.02.2017 Version number 1 Revision: 23.02.2017

	(Contd. of page
· Transport/Additional information:	
$\cdot$ ADR	
· Limited quantities (LQ)	IL
$\cdot$ Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	(D/E)
· IMDG	
· Limited quantities (LQ)	1 L
$\cdot$ Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, I

### **SECTION 15: Regulatory information**

- $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### · Department issuing SDS:

LOGAR Günther Hasel e.K.

Baden-Airpark, Airport Boulevard B 210

D-77836 Rheinmünster Tel: +49(0)7229-1868-163 Fax: +49(0)7229-1868-165

· Contact: info@logar.de

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2

(Contd. on page 8)





Version number 1 Revision: 23.02.2017 Printing date 23.02.2017

(Contd. of page 7)

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3