Version number 1 Revision: 13.03.2017 Printing date 13.03.2017 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: TopDent Hitzeblocker / Lötschutzpaste / Wärmestop · Article number: according to Catalog · 1.2 Relevant identified uses of the substance or mixture and uses advised against · Sector of Use SU20 Health services • Environmental release category ERC2 Formulation into mixture · Application of the substance / the mixture Dental material · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Kentzler-Kaschner Dental GmbH Mühlgraben 36 D-73479 Ellwangen Tel: +49/7961/90730 Fax: +49/7961/52031 E-Mail: info@kkd-topdent.de · Further information obtainable from: During normal business hours Monday-Thursday 08:30 - 12:30 and 13:00 - 16:30 CET Friday 08:30 - 12:30 and 13:00 - 15:00 CET • 1.4 Emergency telephone number: Vergiftungs-Informations-Zentrale Freiburg, Tel. +49 761 19240 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008
 The product is not classified according to the CLP regulation.

· 2.2 Label elements

KASCHNE **DENTA**

- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Dental material

· Dangerous components:		
CAS: 1344-09-8 Silicic acid, sodium salt	15-20%	
EINECS: 215-687-4 Seye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; S H335	TOT SE 3	
CAS: 7647-01-0 hydrogen chloride	3-4%	
EINECS: 231-595-7 🔗 Skin Corr. 1B, H314; 🕩 STOT SE 3, H335		
• Additional information: For the wording of the listed hazard phrases refer to section 16.	GB	

(Contd. on page 2)

Printing date 13.03.2017

Version number 1

Revision: 13.03.2017

Trade name: TopDent Hitzeblocker / Lötschutzpaste / Wärmestop

(Contd. of page 1)

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Take affected persons out of danger area and lay down.

Do not leave affected persons unattended.

No special measures required.

Take affected persons out into the fresh air.

· After inhalation: Take affected persons into fresh air and keep quiet.

- · After skin contact: If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Inform doctor. Do not give milk or fatty oils.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Carbon dioxide (CO2)
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- \cdot 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special measures required.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: None.

(Contd. on page 3)



Printing date 13.03.2017

Version number 1

Revision: 13.03.2017

Trade name: TopDent Hitzeblocker / Lötschutzpaste / Wärmestop

· Storage class: Storage group: 11

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

7647-01-0 hydrogen chloride

WEL Short-term value: 8 mg/m³, 5 ppm Long-term value: 2 mg/m³, 1 ppm (gas and aerosol mists)

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.
- · Respiratory protection:

DGUV 112-190 Breathing apparatus

Filter type A2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Fluorocarbon rubber (Viton)

Butyl rubber, BR

Recommended material thickness:

Butylkautschuk: 0,50 mm +/- 0,10 mm

Fluorkautschuk: 0,75 mm +/- 0,10 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Basis: DGUV 212-007

Permeation (Fluorkautschuk): + Level 6 (> 240 min)

Permeation (Butykautschuk): + Level 6 (> 480 min)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

 \cdot For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton) Butyl rubber, BR

· Not suitable are gloves made of the following materials: Plastic gloves

(Contd. on page 4)



(Contd. of page 2)

GB -

Printing date 13.03.2017

Version number 1

Revision: 13.03.2017

Trade name: TopDent Hitzeblocker / Lötschutzpaste / Wärmestop

(Contd. of page 3)

· Eye protection:

Tightly sealed goggles

Goggles recommended during refilling

9.1 Information on basic physical and ch	nemical properties	
General Information		
Appearance:		
Form:	Fluid	
Colour:	Various colours	
Odour: Odour threshold:	Light Not determined.	
	12.	
pH-value at 20 °C:	12	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range:	Undetermined.	
Flash point:	Not applicable.	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:		
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not determined.	
Density at 20 °C:	1.37 g/cm ³	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Fully miscible.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Viscosity: Dynamic:	Not determined.	
Dynamic: Kinematic:	Not determined.	
ктетинс:	noi aeierminea.	
Solvent content:		
Organic solvents:	0.0 %	



Printing date 13.03.2017

Version number 1

Revision: 13.03.2017

Trade name: TopDent Hitzeblocker / Lötschutzpaste / Wärmestop

(Contd. of page 4)

• 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- \cdot 10.4 Conditions to avoid Open fire, hot surfaces, high temperatures

• 10.5 Incompatible materials: oxidants, acids, bases

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

- Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Smaller quantities can be disposed of with household waste.

(Contd. on page 6)

GB



Printing date 13.03.2017

KASCHNI **Denta**

Version number 1

Revision: 13.03.2017

Trade name: TopDent Hitzeblocker / Lötschutzpaste / Wärmestop

(Contd. of page 5)

· Waste disposal key: 070199 Waste, n.o.s

· European waste catalogue

07 07 99 wastes not otherwise specified

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport informat	ion
· 14.1 UN-Number	Not applicabel
· 14.2 UN proper shipping name	Not applicable
· 14.3 Transport hazard class(es)	Not applicabel
· 14.4 Packing group	Not applicable
· 14.5 Environmental hazards:	Not applicable.
\cdot 14.6 Special precautions for user	Not applicable.
• 14.7 Transport in bulk according to Anne Marpol and the IBC Code	ex II of Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· ADR · Remarks:	No Dangerous Goods
· IMDG · Remarks:	No Dangerous Goods
· IATA · Remarks:	Not restricted

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I hydrogen chloride

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

• Department issuing SDS:

LOGAR Günther Hasel e.K. Baden-Airpark, Airport Boulevard B 210

Version number 1

Revision: 13.03.2017

Trade name: TopDent Hitzeblocker / Lötschutzpaste / Wärmestop

Printing date 13.03.2017

(Contd. of page 6) D-77836 Rheinmünster Tel: +49(0)7229-1868-163 Fax: +49(0)7229-1868-165 · Contact: info@logar.de · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 GB

