

Printing date 22.02.2017 Version number 1 Revision: 22.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: TopDent Schnellkleber dünnflüssig/regular
- · Article number: according to Catalog
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU20 Health services
- · Environmental release category ERC2 Formulation into mixture
- · Application of the substance / the mixture Dental material
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kentzler-Kaschner Dental GmbH

Mühlgraben 36 D-73479 Ellwangen Tel: +49/7961/90730 Fax: +49/7961/52031 E-Mail: info@kkd-topdent.de

· Further information obtainable from:

During normal business hours

Monday-Thursday 08:30 - 12:30 and 13:00 - 16:30 CET

Friday 08:30 - 12:30 and 13:00 - 15:00 CET

• 1.4 Emergency telephone number: Vergiftungs-Informations-Zentrale Freiburg, Tel. +49 761 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

ethyl 2-cyanoacrylate

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)



Printing date 22.02.2017 Version number 1 Revision: 22.02.2017

Trade name: TopDent Schnellkleber dünnflüssig/regular

(Contd. of page 1)

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Dental material

· Dangerous components:			
CAS: 7085-85-0	ethyl 2-cyanoacrylate	80-100%	
EINECS: 230-391-5	🗘 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Take affected persons out of danger area and lay down.

Do not leave affected persons unattended.

Take affected persons out into the fresh air.

· After inhalation:

Take affected persons into fresh air and keep quiet.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Inform doctor. Do not give milk or fatty oils.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 3)



Printing date 22.02.2017 Version number 1 Revision: 22.02.2017

Trade name: TopDent Schnellkleber dünnflüssig/regular

(Contd. of page 2)

- · 5.2 Special hazards arising from the substance or mixture Carbon dioxide (CO2)
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions: No special measures required.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: VCI: 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

7085-85-0 ethyl 2-cyanoacrylate

WEL | Short-term value: 1.5 mg/m³, 0.3 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 4)



Printing date 22.02.2017 Version number 1 Revision: 22.02.2017

Trade name: TopDent Schnellkleber dünnflüssig/regular

(Contd. of page 3)

· Respiratory protection:

DGUV 112-190 Breathing apparatus

Filter type A2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Fluorocarbon rubber (Viton)

Butyl rubber, BR

Recommended material thickness: Butylkautschuk: 0,50 mm +/- 0,10 mm Fluorkautschuk: 0,75 mm +/- 0,10 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Basis: DGUV 212-007

Permeation (Fluorkautschuk): + Level 6 (> 240 min) Permeation (Butykautschuk): + Level 6 (> 480 min)

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Butyl rubber, BR

- · Not suitable are gloves made of the following materials: PVC gloves
- · Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- $\cdot \textbf{ 9.1 Information on basic physical and chemical properties}$
- · General Information
- · Appearance:

Form: Fluid
Colour: Colourless
Odour: Pungent
Odour threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 5)



Printing date 22.02.2017 Version number 1 Revision: 22.02.2017

Trade name: TopDent Schnellkleber dünnflüssig/regular

		(Contd. of page
· Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. 2: 150°C	
· Flash point:	85 °C	
· Flammability (solid, gas):	Not applicable.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product does not present an explosion hazard.	
· Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Vapour pressure:	Not determined.	
· Density at 20 °C: · Relative density · Vapour density · Evaporation rate	1.04 g/cm ³ Not determined. Not determined. Not determined. Not determined.	
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
· Solvent content: Organic solvents:	0.0 %	
Solids content: · 9.2 Other information	100.0 % No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- $\cdot \textit{Thermal decomposition / conditions to be avoided:} \\$

Temperatures >40 °C

Direct sunlight

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Open fire, hot surfaces, high temperatures
- · 10.5 Incompatible materials: oxidants, acids, bases
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 22.02.2017 Version number 1 Revision: 22.02.2017

Trade name: TopDent Schnellkleber dünnflüssig/regular

(Contd. of page 5)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot \textit{Reproductive toxicity } \textit{Based on available data, the classification criteria are not met.}$
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Generally not hazardous for water
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

07 06 01* aqueous washing liquids and mother liquors

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, ADN, IMDG Void · IATA UN 3334

· 14.2 UN proper shipping name

· ADR, ADN, IMDG Void

(Contd. on page 7)



Printing date 22.02.2017 Version number 1 Revision: 22.02.2017

Trade name: TopDent Schnellkleber dünnflüssig/regular

	(Contd. of page
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG	
· Class	Void
· IATA	
· Class	9 Miscellaneous dangerous substances and articles.
· 14.4 Packing group	
· ADR, IMDG	Void
· IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Annex II	of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
\cdot ADR	
· Remarks:	No Dangerous Goods
· IMDG	
· Remarks:	No Dangerous Goods
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- $\cdot \textit{Named dangerous substances-ANNEX I} \ \textit{None of the ingredients is listed}.$
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

· Department issuing SDS:

LOGAR Günther Hasel e.K.

Baden-Airpark, Airport Boulevard B 210

D-77836 Rheinmünster

Tel: +49(0)7229-1868-163

Fax: +49(0)7229-1868-165

· Contact: info@logar.de

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 8)





Printing date 22.02.2017 Version number 1 Revision: 22.02.2017

Trade name: TopDent Schnellkleber dünnflüssig/regular

(Contd. of page 7)

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- GB